

# SAFETY DATA SHEET

#### 1. Identification

Product identifier	Grain Neutral Spirits, 96%
Other means of identification	
Synonyms	Ethanol, Alcohol, Ethyl alcohol 191 to 193 US proof, Ethyl alcohol DPS (95.5% - 96.5% vol), Ethyl alcohol DS (95.5% - 96.5% vol), Ethyl alcohol VS (95.5% - 96.5% vol)
Recommended use	General purpose solvent.
Recommended restrictions	Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in the US, etc.
Manufacturer/Importer/Supplier/	Distributor information
Company name	Greenfield Global Inc.
Address	6985 Financial Drive
	Missisauga, Ontario L5N 0G3
	Canada
Telephone	(905) 790-7500
Website	http://www.greenfield.com
Emergency phone number	CANUTEC: (613) 996-6666

#### 2. Hazard identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2
Label elements		
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapour. Causes se	erious eye irritation.
Precautionary statement		

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

 Response
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

 Storage
 Store in a well-ventilated place. Keep cool.

 Dispessed
 Dispesse of contents (contents in conservations) is conservationed with level/interactional inclusion.

DisposalDispose of contents/container in accordance with local/regional/national/international regulations.Other hazardsNone known.

Supplemental information

Prevention

### 3. Composition/information on ingredients

None.

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	92.98 - 93.09

Composition comments	All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits.
4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapour.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

#### 8. Exposure controls/personal protection

US. ACGIH Threshold Lim Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (Oo Components	ccupational Health & Safety Code, Sche Type	edule 1, Table 2) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Safety Regulation 296/97,		for Chemical Substances, Occupational Health and
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs ( Components	Reg. 217/2006, The Workplace Safety A Type	nd Health Act) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Ontario OELs. (C Components	ontrol of Exposure to Biological or Che Type	emical Agents) Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Quebec OELs. (N Components	linistry of Labor - Regulation respecting Type	g occupational health and safety) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety R Type	egulations, 1996, Table 21) Value
Ethanol (CAS 64-17-5)	15 minute	1250 ppm
	8 hour	1000 ppm
logical limit values	No biological exposure limits noted fo	r the ingredient(s).
propriate engineering trols	Ventilation rates should be matched to exhaust ventilation, or other engineer	aust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ng controls to maintain airborne levels below recommende e not been established, maintain airborne levels to an ation and safety shower.
=	, such as personal protective equipment Wear safety glasses with side shields (or goggles).	
Eye/face protection	Wear safety glasses with side shields	
Skin protection	Wear appropriate chemical resistant gloves. Butyl rubber or Viton® gloves are recommended. Other suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.	
Hand protection	penetrate the gloves. Frequent chang	e is auvisable.
Hand protection Other	penetrate the gloves. Frequent chang Wear appropriate chemical resistant of	
	Wear appropriate chemical resistant of If engineering controls do not maintain limits (where applicable) or to an acce	clothing. In airborne concentrations below recommended exposure aptable level (in countries where exposure limits have not rator must be worn. Respirator type: Chemical respirator w

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Colourless.
Odour	Alcoholic.
Odour threshold	Not available.
рН	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	73.8 - 100 °C (164.84 - 212 °F)
Flash point	13.0 - 16.0 °C (55.4 - 60.8 °F) Tag closed cup (ASTM D 56)
Evaporation rate	1.7 (butyl acetate = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	
Flammability limit - lower (%)	3.3 Ethanol
Flammability limit - upper (%)	19 Ethanol
Vapour pressure	Not available.
Vapour density	1.56 (Air = 1)
Relative density	0.7882 - 0.8103 (20 °C (68 °F))
Solubility(ies)	
Solubility (water)	Complete
Partition coefficient (n-octanol/water)	0.032 approximate
Auto-ignition temperature	370 °C (698 °F) Ethanol
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Dynamic viscosity	1.35 cP Ethanol
Percent volatile	100 % v/v
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion
Information on likely routes of e	xposure
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged or repeated skin contact may cause drying, cracking, or irritation.

**Eye contact** Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Grain Neutral Spirits, 96%

#### Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Acute toxicity	Not expected to be acutely toxic.		
Components	Species Test Results		
Ethanol (CAS 64-17-5)			
Acute			
Inhalation			
Vapour			
LC50	Rat	117 - 125 mg/l, 4 Hours	
Oral			
LD50	Rat	10470 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may ca	ause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitisatio	n		
Respiratory sensitisation	Not a respiratory sensitiser.		
Skin sensitisation	This product is not expected to	o cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	product or any components present at greater than 0.1% are	
Carcinogenicity			
Canada - Manitoba OELs: d	arcinogenicity		
Ethanol (CAS 64-17-5)		Confirmed animal carcinogen with unknown relevance to humans.	
Reproductive toxicity	Possible reproductive hazard.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be h	narmful.	

### 12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
Chronic			
Algae	NOEC	Marine water algae	1580 mg/l
Fish	NOEC	Freshwater fish	250 mg/l
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours

Components		Species	Test Results		
Other	NOEC	Lemna minor	280 mg/l, 7 days		
Other					
Acute					
Micro-organisms I	LC50	Micro-organisms	5800 mg/l, 4 hours		
Terrestrial					
Acute					
Plant	EC50	Terrestrial plant	633 mg/kg dw		
Persistence and degradability	Expected to b	Expected to be readily biodegradable.			
Bioaccumulative potential					
<b>Partition coefficient n-octand</b> Grain Neutral Spirits, 96%	ol / water (log	<b>Kow)</b> 0.032, (Approx	ximate)		
Mobility in soil	Expected to b	e highly mobile in soil.			
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.				
13. Disposal consideration	IS				
Disposal instructions			iners at licensed waste disposal site. Dispose of gional/national/international regulations.		
Local disposal regulations	Dispose in ac	cordance with all applicable regu	lations.		
Hazardous waste code		The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).				
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.				
14. Transport information					
TDG					
UN number	UN1170				
UN proper shipping name Transport hazard class(es)	ETHANOL SC	DLUTION			
Class	3				
Subsidiary risk	-				
Packing group					
Environmental hazards	No. r Read safety instructions, SDS and emergency procedures before handling.				
IATA	Read Salety II	istructions, SDS and emergency	procedures before nandling.		
UN number	UN1170				
UN proper shipping name	Ethanol Soluti	ion			
Transport hazard class(es)					
Class	3				
Subsidiary risk	-				
Packing group					
Environmental hazards ERG Code	No.				
	3L r Read safety instructions, SDS and emergency procedures before handling.				
IMDG	rioud baroty i	ionactione, obe and emorgeney	procedures solore narraing.		
UN number	UN1170				
UN proper shipping name	ETHANOL SC	DLUTION			
Transport hazard class(es)					
	3				
Class	0				
Class Subsidiary risk	-				
Class	- II No.				

EmS Special precautions for use Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	F-E, S-D Fr Read safety instructions, SDS and emergency procedures before han This product is not intended to be transported in bulk.	dling.
15. Regulatory informatio	n	
Canadian regulations	This product has been classified in accordance with the hazard criteria contains all the information required by the HPR.	a of the HPR and the SDS
Controlled Drugs and Subs	stances Act	
Not regulated. Export Control List (CEPA	1999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed.		
Precursor Control Regulati	ons	
Not regulated.		
International regulations Stockholm Convention		
Not applicable.		
Rotterdam Convention		
Not applicable.		
Kyoto Protocol		
Not applicable. Montreal Protocol		
Not applicable.		
<b>Basel Convention</b>		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	pnents of this product comply with the inventory requirements administered by the e components of the product are not listed or exempt from listing on the inventory	

## 16. Other information

Issue date	24-March-2021
Revision date	-
Version No.	01

This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.